Page 7 of 23 **DRAFT**Permit No. GA0033553

B.2. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

(CONTINUED)

Discharge to Cat Creek - Outfall #001 (31.068727°, -83.207118°):

Parameters	Discharge limitations in mg/L unless otherwise specified	Monitoring Requirements		
		Measurement Frequency	Sample Type	Sample Location
Five-Day Biochemical Oxygen Demand Removal, Minimum (%) (1)	85	See Below	See Below	See Below
Total Suspended Solids Removal, Minimum (%)	85	See Below	See Below	See Below
pH, Daily Minimum – Daily Maximum (Standard Unit)	6.0 - 8.5	One Day/Week	Grab	Effluent
Total Residual Chlorine, Daily Maximum	0.02	One Day/Week	Grab	Effluent
Dissolved Oxygen, Daily Minimum (2)	6.0	One Day/Week	Grab	Effluent
Orthophosphate, as P (3)(5)	Report	One Day/Month	Grab	Effluent
Organic Nitrogen, as N (4)(5)	Report	One Day/Month	Grab	Effluent
Nitrate-Nitrite, as N (4)(5)	Report	One Day/Month	Grab	Effluent
Total Kjeldahl Nitrogen, as N (4)(5)	Report	One Day/Month	Grab	Effluent

- Percent removal shall be calculated from monthly average influent and effluent concentrations. Influent and effluent samples shall be collected at approximately the same time.
- Refer to Part I.C.8. TOTAL SUSPENDED SOLIDS, FIVE-DAY BIOCHEMICAL OXYGEN, DEMAND, AMMONIA, DISSOLVED OXYGEN, TOTAL NITROGEN, AND TOTAL PHOSPHORUS COMPLIANCE SCHEDULE
- Total phosphorus and orthophosphate must be analyzed from the same sample.
- Ammonia, organic nitrogen, nitrate-nitrite, total Kjeldahl nitrogen (TKN), and total nitrogen must be analyzed or calculated from the same sample. Organic nitrogen, as N = TKN ammonia, as N. Total nitrogen is the sum of all nitrogen and calculated as follows: TN = TKN + nitrite + nitrate.
- (5) Refer to Part I.C.9 COMPREHENSIVE NUTRIENT OPTIMIZATION PLAN.