- c. The pathogen density requirements and specific criteria listed in Chapter 391-3-6-.17(7) of the State Rules shall be monitored at the frequency listed in Part IV.A.5 of this permit.
- d. The vector attraction reduction requirements and specific criteria, referenced in the approved SMP, listed in Chapter 391-3-6-.17(8)(a) through (8)(h) of the State Rules shall be monitored at the frequency listed in Part IV.A.5 of this permit.
- 5. The permittee will monitor the sewage sludge as required in Chapter 391-3-6.17(11)(a) of the State Rules at the below frequencies:

Amount of Sludge (1)	Frequency
0-300 dry tons/year	Once/year
300-1,600 dry tons/year	Once/quarter
1,600-16,000 dry tons/year	One/Two months
>16,000 dry tons/year	Once/Month

- The amount of sewage sludge refers to either the amount of bulk sewage sludge (dry weight) applied to the land, or the amount of sewage sludge (dry weight) received by a preparer that sells or otherwise distributes sewage sludge in a bag or other container for application to the land.
- 6. In accordance with Chapter 391-3-6-.17(12) of the State Rules, sewage sludge samples shall be analyzed using EPA approved methods contained in 40 CFR Part 503.8.
- 7. A proposed addition or removal of land application site(s) will be subject to EPD's review and approval process as outlined in the *Guidelines for Land Application of Sewage Sludge (Biosolids)* at Agronomic Rates, June 2006 as amended and in accordance with the State Rules. Upon approval of the SMP or an amendment of a SMP and the corresponding modification of the permit by the Director, the permittee may start land applying treated sewage sludge on the proposed sites.